



4025 2WD - 4WD

4025 2WD-4WD Series Tractors



**FREE 3 YEAR
WARRANTY***

No.1 TRACTOR
COMPANY
IN THE WORLD
BY VOLUME*

Mahindra
Rise.

4025 2WD (41HP)

This economical, rugged utility tractor now offers versatility and ergonomic comfort. Its simplicity and tough-terrain durability make it the perfect high value tractor for everything from material handling, lifting and digging to rotary-cutting and graining.

4025 KEY FEATURES:

- Best-in-class loader lift capacity with quick hitch bucket;
- Mahindra built 4 cylinder wet sleeve engine for big power and long life;
- Simple and strong transmission and rear end components for long, trouble-free life;
- A 1600kgs capacity three-point hitch with draft control standard, allowing customers to do big jobs;
- An easy on and off platform and simple, long-lasting transmission and brakes Mahindra 35 series-style suspension seat.
(suspension seat on **4WD** model only)

Beverage Holder



Differential Lock



4025 4WD (41HP)

The Mahindra 4025, 41 HP Tractor is simple to operate yet provides impressive power. With an overall weight of 2360 kgs in 4WD configuration, the Mahindra 4025 is one of the heaviest and most rugged tractors in its category. The complete equipment package with a large capacity engine, heavy duty transmission, high lift capacity hydraulics and very robust cast iron chassis makes it perfect for everything, from basic chores around the farm to commercial landscaping.

*Suspension Seat
with Armrests*



*1.6 Tonne Lift on
3 point hitching*



**JAPAN
QUALITY
MEDAL
WINNER**

FOR MORE INFORMATION ON MAHINDRA PRODUCTS VISIT:
WWW.MAHINDRA.COM.AU/AG



SPECIFICATIONS

TRACTOR SPECIFICATIONS		
ENGINE	4025 2WD	4025 4WD
Type	Four stroke, direct injection, water-cooled, diesel	Four stroke, direct injection, water-cooled, diesel
Emission	Tier 4 Compliance (Interim)	Tier 4 Compliance (Interim)
Cylinders	4	4
Cylinder Sleeve	Wet replaceable	Wet replaceable
Engine HP (k.W.) @ rpm	41 (30.5) @ 2300	41 (30.5) @ 2300
Compression Ratio	19.5:1	19.5:1
Displacement (cc)	2732	2732
Fuel Tank Capacity	58 Litres	55 Litres
ELECTRICAL		
Battery Capacity	12 volt, 88 amp hours	12 volt, 88 amp hours
Alternator	12 volt, 36 amps	12 volt, 36 amps
CLUTCH		
Type	Dual	Dual
TRANSMISSION		
Type	Sliding mesh	Full Constant mesh
Number of Gears/Speeds	8F / 2R	8F / 2R
STEERING		
Type	Hydrostatic power	Hydrostatic power
Pump Output (lpm)	18.9	18.9
BRAKES		
Type	Fully enclosed dry disc	Fully enclosed dry disc
HYDRAULIC SYSTEM		
Type	Open centre, full-live hydraulic with position and draft controls	Open centre, full-live hydraulic with position and draft controls
Pump Output (lpm)	31.38	33
3-Point Linkage	Category 1 & 2 adjustable with telescopic stabilisers	Category 1 & 2
Lift Capacity (kgs)	1600	1600
Remote Auxiliary Remote Valves	1 spool optional	1 spool optional
PTO		
Type	Rear, 6 Spline, Single Speed, CRPTO	Rear, 6 Spline, Single Speed, CRPTO
PTO RPM (engine rpm)	540 @ 2058	540 @ 2058
PTO HO	31 (23.1)	31 (23.1)
OPERATING WEIGHT		
Total Weight	1990 kgs	2360 kgs
DIMENSIONS		
Overall Length (mm)	2928	3290
Overall Width (mm)	1762	2090
Turning Radius (mm)	2900	6400
WHEELS & TYRES	AG (Standard)	Industrial (Standard) AG (Optional)
Front	6 x 16	12 x 16.5 9.5 x 16 (Optional)
Rear	12.4 x 28	16.9 x 24 12.4 x 28 (Optional)

LOADER SPECIFICATIONS	
LOADER	ML345
TRACTOR MODEL	4025 2WD - 4WD
Self Level Mechanism	Yes
Maximum Lift Height	2610 mm
Clearance Attachment Level	2396 mm
Clearance Bucket Dumped	1859 mm
Reach at Maximum Height	354 mm
Maximum Dump Angle	58°
Reach with Attachment on Ground	1595mm
Attachment Rollback Angle	36°
Digging Depth Below Grade	80 mm
Overall Height Carry Position	1627 mm
Depth of Attachment (to back of inner shell)	591 mm
Height Attachment	544 mm
Length Attachment (to pivot pin)	768 mm
Lift Capacity Full Height Pivot Pins	1310 kgf
Breakout Force Ground Level, Pivot Pins	2173 kgf
Relief Valve Setting (Loader Control Valve)	180 kg/cm2
Attachment Used For Specification	1520 mm
Bucket Capacity	0.274 cu.m
Hydraulic System	Tractor pump with loader control valve
Bucket Level indicator	Standard
Optional Attachments	Grill guard, Suitcase Front weight Package

Photographs may show overseas models or illustrate non-standard equipment. Please read your Mahindra Tractor manual carefully prior to operation. ^3 Year Engine & Powertrain warranty. #Mahindra & Mahindra Ltd is the No.1 Tractor company in the world by volume. Information subject to change without notice.

Dealer Details:



Tel: 03 5339 2056
206 Burnbank Street,
Wendouree, VIC, 3355

www.ngaautogroup.com.au

FIND US ON FACEBOOK
[FACEBOOK.COM/MAHINDRAAG](https://www.facebook.com/MAHINDRAAG)