



NOW OFFERING

7 YEAR POWERTRAIN WARRANTY^A

THE ALL NEW eMax 25s

- Steel Bonnet & Chassis
- Better stability on hills
- Robust Drawbar and Cat 1 linkage
- Industry leading Loader lift capacity & tractor weight
- Industry leading Linkage lift capacity & hydraulic flow
- Fender mounted controls & cup holder



Mahindra
Rise.

MAIN FEATURES

The Mahindra eMax 25s series feature a full-length tractor frame that allows customers to install a wide range of attachments including: a 60 inch Mowing deck, Backhoe, Self-Level loader, 4in1 bucket, Slashers, Carryalls, Rotary tillers, Box scraper blades and Post hole diggers.

Mower Specifications

MOWER MODEL	eMax 25M
Cutting Width	1524mm [60"]
Cutting Height	508mm [2in] to 1143mm [4.5in]
Blade Tip speed	17,350 ft/min
Deck Shell Thickness	10 Gauge
Double Deck thickness at blade spindles	YES
Fabricated or stamped deck	STAMPED
Weight mounted	152kg

Backhoe Specifications

BACKHOE MODEL	MBH-22
Maximum Digging Depth	1938mm [76.3"]
Digging Depth [610mm] Flat Bottom	1902mm [74.9"]
Overall Operating Height - Fully Raised	2662mm [104"]
Loading Height [bucket @ 60°]	1575mm [62"]
Loading Reach [bucket @ 60°]	914mm [36"]
Reach From Swing Post	2591mm [102"]
Bucket Rotation	180°
Swing Arc	150°
Stabiliser Spread Operating Position	1880mm [74"]
Stabiliser Down Below Grade	152mm [6"]
System Relief Valve Setting	2000
Digging Force - Bucket	2145lb
Digging Force - Dipper	903lb



eMax 25s Series Standard Features

3 POINT LINKAGE

3 Point Linkage standard like all true tractors. Allows for hook up of a greater range of true size implements. Standard 540 RPM PTO.



DRIVE OVER MOWER

Drive Over Steel Stamped 60-inch Mower Deck with deck lift height up to 1143mm [4.5 inch].



CONVENIENCE

Creature comforts like side by side forward/reverse, cup holder and cruise control all come standard.



The new eMax 25s changes the game again!

The first generation of Mahindra Max small tractors set a new standard in terms of longevity, performance, versatility and ease-of-use, and now this latest Mahindra eMax25s range is set to again shift the bar for tractor performance and durability in the small tractor market.

The all new eMax 25s includes an impressive list of features, starting with the grunty and reliable 25 horsepower Tier IV-compliant engine, with no DPF meaning no expensive diesel particulate filters.

The tough, steel construction of the tractor yields a weight of 730kg. This doesn't just mean it lasts longer, it means that in combination with a wide track and the longer footprint of the eMax 25s standard Titan USA wheel equipment, it provides an important increase in operational stability on challenging gradients.

The eMax 25s features a linkage lift capacity and hydraulic flow which is the best in the industry, as well as a robust drawbar and Cat 1 linkage standard – not a garden hitch.

There's also an industry-leading loader lift capacity of 250kg Safe Working Load, and linkage lift capacity of 600kg when correctly ballasted, so you work smarter, not harder.



SUPERIOR PERFORMANCE. GREATER VALUE.

- Professional grade construction = Bigger, thicker, more solid components
- Heavier, sturdier chassis = Greater traction, stability & safety
- Superior lift capacity = Lift heavier loads
- 7 year/2000hr warranty = Peace of mind

No.1 TRACTOR
COMPANY
IN THE WORLD BY VOLUME*

Proven Quality – JAPAN QUALITY MEDAL WINNER

Quality is paramount at Mahindra and we are proud to be the first and only tractor manufacturing company in the world to win the Japan Quality Medal (JQM), a laurel truly hard to earn. It is universally acclaimed as the highest award presented to a company following Total Quality Management (TQM) practices in their entire business operations. JQM recognizes a high level of customer focus, improvements in overall quality and excellence in business processes.

Also, Mahindra was the first tractor company worldwide to win the Deming Application Prize in 2003 for excellence in quality, making it the only tractor manufacturer to receive both distinctions.



**JAPAN
QUALITY
MEDAL
WINNER**

SPECIFICATIONS

MODEL	eMax 25s HST
ENGINE	
Engine HP (kw) - Gross	24 (17.8)
PTO HP (kw)	19.3 (14.17) (max)
Rated engine speed	3000
Number of cylinders	3
Displacement - cc (cu.in.)	1007 (61.5)
Air cleaner	Dry Element
ELECTRICAL SYSTEM	
Alternator	12V.50A
FUEL SYSTEM	
Type	Direct Fuel Injection
DRIVETRAIN	
Transmission type	HST
Number of speeds	2 Range
Max traveling speed - km/h (mph)	16.4 (10.2)
Brakes	Wet Disc
Steering	Hydrostatic
HYDRAULIC SYSTEM	
Pump (type)	Gear Pump
Implement pump capacity - L/min (gpm)	17 (4.5)
Steering pump capacity - L/min (gpm)	10 (2.64)
Maximum total flow - L/min (gpm)	27 (7.1)
Category, 3 point hitch	1
Hitch lift capacity - kg (lb)	600 (1323)
at 24 inches behind link ends - kg (lb)	419 (924)
Lift control type	Position
No. of optional remote valves	1
PTO	
Type	Independent
Control	Electric/Hydro
Mid (rpm)	2000
Rear (rpm)	540 @ 2893
Shaft Diameter - mm (in)	35 (1 3/8)
CAPACITIES	
Fuel Tank - Litres (U.S. gal)	25 (6.6)
Cooling System - Litres (U.S. qt)	4 (4.2)
Crankcase (with filter) - Litres (U.S. qt)	3.8 (4.0)
Trans.& Hydr. System - Litres (U.S. gal)	14.5 (5.68)
Front Axle - Litres (qt)	3.5 (3.7)
DIMENSIONS (with standard tyres)	
Overall length - mm (in) with 3P	2563 (100.9)
Overall width - mm (in)	1164 (45.8)
Wheelbase - mm (in)	1460 (57.5)
Height to top of ROPS - mm (in)	2337 (92)
Min. Ground Clearance - mm (in)	260 (10.2)
Min. Turning Radius - mm (in) w/o brakes	2600 (102.3)
STANDARD TYRES	
Agricultural (Optional) Front	6 x 12
Agricultural (Optional) Rear	9.5 x 16
Industrial (Standard) Front	20 x 8-10
Industrial (Standard) Rear	27 x 12.5-15
ROLL-OVER PROTECTIVE STRUCTURES	
Standard	ROPS
WEIGHT	
Total weight - kg (lb)	730 (1610)



eMax 25s versus the others

	eMax 25s	OTHER GUYS	OTHER GUYS
WEIGHT	730 kg	655	665
LINKAGE LIFT	600 kg	309	310
TOTAL FLOW	27 ltr/pm	24	23.5

TRY THE MAHINDRA FLEX TEST



OUR FRAMES DON'T FLEX

Images may show overseas models or non-standard equipment. Specifications & design subject to change without notice. ^7 Year/2000 hour Powertrain warranty, whichever occurs first, applies to Tractor Powertrain, please see your local authorised Mahindra Ag dealer for full Warranty terms and conditions. #Mahindra & Mahindra Ltd is the No.1 Tractor company in the world by volume.

Dealer Details:



Tel: 03 5339 2056
206 Burnbank Street,
Wendouree, VIC, 3355
www.ngaautogroup.com.au